

New Holland 200TL Series Front-End Loader Specifications



210TL 240TL 250TL 260TL 270TL

LOADER MODEL TRACTOR COMPATIBILITY	210TL BOOMER 1030 T1110	240TL BOOMER 2030, 2035 T2210, T2220 (NON SUPERSTEER)	240TL BOOMER 2030, 2035 T2210, T2220 SUPERSTEER	250TL BOOMER 3040, 3045, 3050 T2310, T2320, T2330	260TL BOOMER 3040, 3045 T2310, T2320, T2330	270TL BOOMER 4055, 4060 T2410, T2420
Max. lift height, in. (mm)	72.6 (1844)	98.4 (2499)	98.4 (2499)	105 (2667)	106 (2692)	112.3 (2852)
Dump clearance, in. (mm)	52.2 (1326)	75.3 (1913)	75.7 (1923)	81.5 (2070)	82 (2083)	85.2 (2164)
Digging depth, in. (mm)	2 (51)	8 (203)	8 (203)	6.5 (165)	7 (178)	4.9 (124)
Lift capacity, lbs. (kg)						
@ bucket pivot point	900 (408)	1,250 (567)	1,250 (567)	2,000 (907)	1,955 (887)	2,500 (1134)
@ 19.7 in. (500 mm)						
from bucket pivot point	537 (244)	890 (403)	1,183 (537)	1,540 (699)	1,545 (701)	1,830 (830)
Breakout force, lbs. (kg)						
@ bucket pivot point	1,492 (677)	2,700 (1224)	2,700 (1224)	3,540 (1606)	3,254 (1476)	5,000 (2268)
@ 19.7 in. (500 mm)						
from bucket pivot point	1,084 (492)	1,900 (862)	1,900 (862)	2,640 (1198)	2,470 (1120)	3,114 (1413)
Reach at max. lift, in. (mm)	27.8 (706)	31 (787)	39 (991)	33 (838)	43 (1092)	32 (813)
Bucket rollback, degrees	23	32	32	30	32	39
Bucket dump angle degrees	43	39	39	58	60	49

Visit our Web site at www.newholland.com/na. Or, call toll-free **866-NEW-HLND (866-639-4563)**.

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.