

New Holland 400GM Series Flex-Wing Finishing Mower Specifications



410GM 420GM 430GM

MODEL	410GM	420GM	430GM
PACKAGE	100	200	300
SIZE, in. (mm)	60 (1524)	72 (1829)	90 (2286)
Overall cutting width, ft. (m)	12 (3.7) Flex	15 (4.6) Flex	17 (5.2) Flex
Center deck cutting width, ft. (m)	5 (1.5)	6 (1.8)	7.5 (2.3)
Wing deck cutting width, ft. (m)	4 (1.2)	5 (1.5)	6 (1.8)
Deck overlap, in. (mm)	6 (152)	6 (152)	12 (305)
Overall width, in. (mm)	146 (3708)	182 (4623)	207 (5258)
Transport width, in. (mm)	100 (2540)	101 (2565)	102 (2591)
Maximum overall length, in. (mm)	182 (4623)	185 (4699)	196 (4978)
Transport length, in. (mm)	177 (4496)	180 (4572)	188 (4775)
Transport height, in. (mm)	90 (2286)	100 (2540)	110 (2794)
Min. hp (kW)	30 (22.4)	35 (26.1)	40 (29.8)
Cutting height range, in. (mm)	1 to 5 (25 to 127)		
Blasé tip speed, FPM (mpm)	16,000 (4877)		
Caster wheels, 12	15 x 6.00-6		
Transport tires, 2	26 x 12.00-12		
Approx. weight, lbs. (kg)	2600 (1179)	2800 (1270)	3100 (1406)

Visit our Web site at www.newholland.com/na. Or, call toll-free **866-NEW-HLND (866-639-4563)**.

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.