

New Holland Forage Blower Specifications

F62B



MODEL	F62B
LENGTH	108 in. (2,743 mm)
WIDTH	100 in. (2,540 mm)
WEIGHT	1,605 lbs. (729 kg)
BLOWER	
Blowing height*	Over 100 ft. (Over 30 m)
Blower housing	60 in. dia. (1,524 mm)
Paddles (adjustable)	8
Paddle tip speed	8,460 ft./min. (2,579 m/min.)
Drive	Direct PTO
HOPPER	
Diameter	Auger—12 in. (305 mm)
Length	Auger—50 in. (1,270 mm)
Width	37 in. (940 mm)
Height from ground	Adjustable—20½ in. (520 mm) to 27½ in. (699 mm)
Feeder type	Auger
DRIVELINE PROTECTION	Shearbolt
PTO	540 rpm
TIRES	4.80–8 "C" load range
CAPACITY (with adequate power)	
Corn silage*	Up to 180 tons/hr. (163 mt/hr.)
Haylage*	Up to 110 tons/hr. (100 mt/hr.)
OPTIONAL EQUIPMENT	Pipe Clamp Kwik Pipe Bundle Telescoping Pipe Section Hinged Deflector Safety Tow Chain+

* Capacity and height will depend upon tractor horsepower, type of crop, moisture content, length of cut, as well as general maintenance of pipes and spout.
+ Available from New Holland Service Parts.

Visit our Web site at www.newholland.com/na. Or, call toll-free **866-NEW-HLND (866-639-4563)**.

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.