

LT SERIES LT85A • LT95A

**AGCO**  
TRACTORS



| MODEL  | LT85A                      | LT95A                      |
|--|----------------------------|----------------------------|
| <b>Configuration</b>                             |                            |                            |
| Drive System                                     | 2WD or 4WD                 | 2WD or 4WD                 |
| Operator Area                                    | Platform or Cab            | Platform or Cab            |
| <b>Performance</b>                               |                            |                            |
| PTO HP (kW) @ Rated Engine RPM                   | 85 (63) @ 2200             | 95 (71) @ 2200             |
| Fuel Tank Capacity gal (L)                       | 38 (145)                   | 38 (145)                   |
| Optional Fuel Tank gal (L)                       | 17 (65)                    | 17 (65)                    |
| <b>SisuDiesel Engine</b>                         |                            |                            |
| Number of Cylinders/Aspiration                   | 4/Turbocharged/Intercooled | 4/Turbocharged/Intercooled |
| Type of Cooling/Fuel                             | Water/Diesel               | Water/Diesel               |
| Displacement in <sup>3</sup> (L)                 | 269 (4.4)                  | 269 (4.4)                  |
| Starting Aid                                     | Grid Heater                | Grid Heater                |
| <b>Transmission</b>                              |                            |                            |
| Auto-4   | 4-speed Powershift         | 4-speed Powershift         |
| Speeds - Forward/Reverse                         | 16F/16R                    | 16F/16R                    |
| Multi-Function Power Shuttle                     | Standard                   | Standard                   |
| Creep  | Optional                   | Optional                   |
| <b>Brakes and Final Drives</b>                   |                            |                            |
| Type of Final Drives                             | Inboard Planetary          | Inboard Planetary          |
| Type of Brakes                                   | Wet Disc                   | Wet Disc                   |
| <b>PTO</b>                                       |                            |                            |
| Speeds RPM                                       | 540 & 1000 Standard        | 540 & 1000 Standard        |
| Optional   | Economy PTO                | Economy PTO                |
| Engagement                                       | Electrohydraulic           | Electrohydraulic           |
| <b>2WD Front Axle</b>                            |                            |                            |
| Standard   | Heavy-Duty Telescopic      | Heavy-Duty Telescopic      |
| <b>4WD Front Axle</b>                            |                            |                            |
| Engagement                                       | Electrohydraulic           | Electrohydraulic           |
| Maximum Steering Angle                           | 55°                        | 55°                        |
| <b>Hydraulics</b>                                |                            |                            |
| System Type – Std/Opt                            | Open Center/Closed Center  | Open Center/Closed Center  |
| Flow @ Remotes – Open Center gpm (lpm)           | 26 (100) Std/15 (57) Opt   | 26 (100) Std/15 (57) Opt   |
| Flow @ Remotes – Closed Center gpm (lpm)*        | 29 (110)                   | 29 (110)                   |
| Remotes – Std/Opt                                | 2/4                        | 2/4                        |
| <b>Three-Point Hitch</b>                         |                            |                            |
| Category   | II                         | II                         |
| Stabilizers                                      | Telescopic                 | Telescopic                 |
| Lift Capacity @ 24 in (610 mm) lbs (kg)          | 7,817 (3,545)              | 7,817 (3,545)              |
| Optional Lift Capacity @ 24 in (610 mm) lbs (kg) | 9,189 (4,168)              | 9,189 (4,168)              |

\*Cab Only \*\*Requires Closed Center Hydraulics

| <b>Operator Area</b>                             |                      |                      |
|--|----------------------|----------------------|
| Cab Glass Area ft <sup>2</sup> (m <sup>2</sup> ) | 61 (5.6)             | 61 (5.6)             |
| Steering Wheel (Cab Models Only)                 | Tilt & Telescopic    | Tilt & Telescopic    |
| Operator Seat (Cab) Standard/Optional            | Mechanical/Air       | Mechanical/Air       |
| Operator Seat (Platform)                         | Mechanical           | Mechanical           |
| Transmission Control Location                    | Right Console        | Right Console        |
| Forward/Reverse Shuttle Location                 | Left Steering Column | Left Steering Column |
| Cab Doors Standard                               | 2                    | 2                    |
| <b>Dimensions and Weight</b>                     |                      |                      |
| Wheelbase in (mm)                                | 105.1 (2,670)        | 105.1 (2,670)        |
| Overall Length in (mm)                           | 172 (4,368)          | 172 (4,368)          |
| Maximum Height Over Cab in (mm)                  | 110 (2,802)          | 110 (2,802)          |
| Height Over Folded ROPS in (mm)                  | 62.5 (1,587)         | 62.5 (1,587)         |
| Approx. Weight 2WD Platform lbs (kg)             | 8,480 (3,847)        | 8,480 (3,847)        |
| Approx. Weight 4WD Platform lbs (kg)             | 9,190 (4,169)        | 9,190 (4,169)        |
| Approx. Weight 2WD Cab lbs (kg)                  | 8,880 (4,082)        | 8,880 (4,082)        |
| Approx. Weight 4WD Cab lbs (kg)                  | 9,590 (4,349)        | 9,590 (4,349)        |

### LOADER SPECIFICATIONS

#### AGCO FL40A Loader (Premium Non-Self-Leveling)

|   |
|---|
| 148 in (3.7 m) Lift Height  |
| 3,190 lbs (1447.0 kg) Lift Capacity @ 31.5 in (800 mm) Forward Pivot Pins |
| Quick Lock System for Loader & Attachments                                |

#### Optional Equipment:

|  |
|--|
| Softdrive System (Hydraulic Load Dampening System)     |
| Live Third Function** or Third Function Diverter Valve |

#### AGCO FL45A Loader (Mechanical Self-Leveling)

|   |
|---|
| 148 in (3.7 m) Lift Height  |
| 3,410 lbs (1547 kg) Lift Capacity @ 31.5 in (800 mm) Forward Pivot Pins |
| Quick Lock System For Loader & Attachments                              |

#### Optional Equipment:

|  |
|--|
| Softdrive System (Hydraulic Load Dampening System)     |
| Live Third Function** or Third Function Diverter Valve |

#### AGCO FL400A Loader (Standard Loader)

|   |
|---|
| 148 in (3.7 m) Lift Height  |
| 3,500 lbs (1588 kg) Lift Capacity @ 31.5 in (800 mm) Forward Pivot Pins |
| Quick Attach Pedestal Mount   |
| Quick Lock System for Loader & Attachments                              |

#### Optional Equipment:

|                               |
|-------------------------------|
| Hydraulic Self-Leveling       |
| Third Function Diverter Valve |

Printed in the U.S.A. AGCO, may at any time, and from time to time, for technical or other necessary reasons, modify any of the data, specifications or warranty of the products described herein. Some equipment shown may be optional. The information contained in this brochure is intended to be of a general nature only, specific operations may vary from the average, and both crop and machine management, as well as the weather, are important factors in the end result. Attention: Photographs in this publication may show protective shields or guards open or removed for the purposes of illustration. Be certain all shields and guards are in place during operation. AG08157 (04)5 PD

Information on other AGCO products available at [www.agcoiron.com](http://www.agcoiron.com).

AGCO Corporation • 4205 River Green Parkway, Duluth, GA 30096 • Phone 800.767.3221  
Fax 770.813.6038 • [www.agcocorp.com](http://www.agcocorp.com) • AGCO is a Reg. TM of AGCO Corporation  
©2007 AGCO Corporation



Play It Safe. Work Safely.