



LANDOLL®

Model 2000

Row Crop Cultivator



MINIMUM TILL - NO-TILL - RIDGE-TILL - CONVENTIONAL
The answer to all of your row crop needs



Row Crop Cultivator

Specifications

MODEL NO.	NO.OF ROWS	ROW SPACING	APPROX. WEIGHT	TRANSPORT HEIGHT	TRANSPORT WIDTH
RIGID FRAME MODELS					
2004-30	4	30"	2100		11'0"
2004-36	4	36"/38"	2225		13'6"
2006-30	6	30"	3000		16'0"
2006-36	6	36"/38"	3131		20'0"
2008-30	8	30"	3872		21'0"
2008-36	8	36"/38"	4046		26'3"
2008-40	8	40"	4089		27'8"
2010-30	10	30"	5500		26'3"
FLAT FOLDING MODELS					
2006-36F	6	36"/38"	3989	9'10"	11'6"
2008-30F	8	30"	4730	9'10"	12'0"
2008-36F	8	36"/38"	4905	9'10"	15'0"
2008-40F	8	40"	4948	9'10"	16'5"
2010-30F	10	30"	5900	9'10"	17'2"
2012-30F	12	30"	6700	9'10"	17'2"
2012-36F	12	36"/38"	8158	11'10"	21'3"
2012-38F	12	38"	8223	11'10"	23'0"
2012-40F	12	40"	8277	11'10"	22'6"
2016-30F	16	30"	8663	11'10"	22'6"

STANDARD EQUIPMENT:

- 7" X 7" Heavy Wall Toolbar
- Wide Parallel Linkage with Heavy Duty Down Pressure Springs
- 6" X 4" Gang Frames
- 20" Adjustable Coulters
- 16" Penetrator Sweeps on 30" Rows
- 24" Penetrator Sweeps on 36/38" Rows
- Fork-Mounted Gauge Wheels with 4.6" x 16" Hard Rubber Tires
- CAT II 3 Pt Hitch for 4-8 Row Units
- CAT III 3 Pt Hitch for 10-16 Row Units

AVAILABLE OPTIONS

- Shields
- 4" Ridgers
- 8" Ridgers (Irrigations)
- Anhydrous Kit Assemblies
- 14" Disc Hillers
- Liquid Fertilizer Spray Attachments
- Lift Assist Wheels
- Row Crop Tank Hitch



Landoll Corporation
1900 North Street
Marysville, KS 66508



www.landoll.com

(800)428-5655

Continuous product improvement is a Landoll goal. Therefore, we reserve the right to make any changes in illustrations, specifications, equipment and prices without prior notice and without changes on previous models.

Printed In U.S.A.

LAN2000-0106