



LANDOLL®

Model 2210

Weatherproofer I



Model 2215-6-30 with Straight Leg Shanks



Model 2217-7-30 with Parabolic Shanks

Landoll's double offset tandem disc gangs assure you 100% disc cut in front of the shanks. Landoll offers 22" diameter by 1/4" disc blades with Rock-Flex protection. Optional 24" diameter by 1/4" disc blades are available.

Coil spring automatic reset clamps with parabolic (37" x 1-1/8" x 3") or heavy duty straight leg (37" x 1-1/4" x 4") shanks with slide on roll pin points. Shanks work up to 18" deep. If an obstacle is encountered, the shank will trip up to 14" and reset automatically.

Unique disc cut angle settings allow for adjusting of all four gangs. Choose from 10, 15 or 20 degree cutting angle to leave the amount of residue preferred for conservation compliance. Landoll offers you a choice of 24" or 30" shank spacing. Sizes available from 3 shank to 9 shank.

Cut and size residue and deep-till compaction zones all in one pass.



2210 Weatherproofer

Standard Specifications

- FRAME:**
- 6 x 3 Heavy wall tubing on 2215
 - 6 x 4 Heavy wall tubing on 2217
- DISC GANGS:**
- Double offset tandem disc gangs
 - Re-greaseable disc bearings
 - 20" Feathering blades
 - 22" Disc blades
 - 15" Disc spacing
 - Up to 6" cutting depth
 - Three disc cutting angles - 10, 15, or 20 degrees
- SHANKS:**
- Two shank options, parabolic or straight leg shanks
 - Coil spring auto-reset shank protection
- HITCH:**
- Long T-Type hitch
 - Cat III pintle clevis
 - Level lift linkage
 - Radius rod to level machine
- AXLES/ROCKSHAFT:**
- Single axles on 2215
 - Walking tandems on 2217
 - Hydraulic lift w/4 x 10 cylinders
- OTHER:**
- Hydraulic hoses to tractor (with couplers)
 - Wrenches for gang bolt and angle adjustment
 - Storage trays
 - Warning lights

Model Specifications

Model Number	Number of Shanks	Shank Spacing	Number of Discs	Transport Width	Working Width	Walking Tandems
2215-3-30	3	30	16	9'0"	9'0"	No
2215-4-24	4	24	16	9'0"	9'0"	No
2215-4-30	4	30	20	11'4"	11'4"	No
2215-5-24	5	24	20	11'4"	11'4"	No
2215-5-30	5	30	24	13'8"	14'2"	No
2215-5-30 D*	5	30	24	13'8"	14'2"	Yes
2215-6-30	6	30	28	16'0"	16'0"	No
*Denotes Dual Wheels						
2217-5-30	5	30	24	14'2"	14'2"	Yes
2217-6-30	6	30	28	16'0"	16'0"	Yes
2217-7-24	7	24	24	14'2"	14'2"	Yes
2217-7-30	7	30	32	18'4"	18'4"	Yes
2217-8-30	8	30	36	20'9"	20'9"	Yes
2217-9-24	9	24	32	18'4"	18'4"	Yes



Landoll Corporation
 1900 North Street
 Marysville, KS 66508



www.landoll.com

(800)428-5655

Continuous product improvement is a Landoll goal. Therefore, we reserve the right to make any changes in illustrations, specifications, equipment and prices without prior notice and without changes on previous models.

Printed In U.S.A.

LAN2210-0106