

# New Holland Posthole Digger Specifications

906



MODEL	906 LIGHT DUTY	906 MEDIUM DUTY	906 HEAVY DUTY
Hitch category	I	I or II	I or II
Input rpm on PTO.....		540	
Max. tractor PTO horsepower	35 hp	55 hp	90 hp
Drive protection .....		shear bolt	
Output shaft diameter, in. (mm).....		2 (50.8)	
Maximum digging depth (less extensions), in. (mm)			
Without extensions .....		42 (1066.8)	
With 9-inch extension .....		51 (1295.4)	
With 14-inch extension.....		56 (1422.4)	
Square steel tube diameter			
Boom, in. (mm).....		3 (76.2)	
Mast, in. (mm).....		3.5 (88.9)	
Down pressure kit	n/a	n/a	optional
Weight, lbs. (kg)	235 (106.6)	260 (117.9)	335 (152.0)
<b>AUGERS</b>			
Semi-double flight, in. (mm).....		6 (152.4)	
.....		9 (228.6)	
.....		12 (304.8)	12 (304.8)
Double flight, in. (mm).....		9 (228.6)	
.....		12 (304.8)	12 (304.8)
.....		14 (355.6)	14 (355.6)
.....		18 (457.2)	18 (457.2)
.....			24 (609.6)

Visit our Web site at [www.newholland.com/na](http://www.newholland.com/na). Or, call toll-free **866-NEW-HLND (866-639-4563)**.

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.