	T110	T140	T180	T190	T250	T250 (Rolle	T250 (Steel	T300	T300 (Rolle	T300 (Steel	T320	T320 (Rolle	T320 (Steel Tracks)		
Emissions Tier (EPA)	Interim Tier 4	Interim Tier 4	Interim Tier 4	Interim Tier 4	Tier 3	Tier 3	Tier 3	Tier 3	Tier 3	Tier 3	Tier 2	Tier 2	Tier 2		
Engine Fuel	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel		
Horsepower	41.8 HP	49 HP	66 HP	66 HP	81 HP	81 HP	81 HP	81 HP	81 HP	81 HP	92 HP	92 HP	92 HP		
Turbocharged Engine	No	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes		
Rated Operating Capacity (SAE)	1100 lbs	1400 lbs	1800 lbs	1900 lbs	2500 lbs	2307 lbs	2500 lbs	3000 lbs	2832 lbs	2700 lbs	3100 lbs	2832 lbs	2700 lbs		
Operating Capacity (50% of Tip)	1595 lbs	2022 lbs	2748 lbs	3642 lbs	3679 lbs	3296 lbs	3476 lbs	4604 lbs	4046 lbs	3870 lbs	4604 lbs	4046 lbs	3870 lbs		
Tipping Load	3190 lbs	4044 lbs	5496 lbs	7283 lbs	7358 lbs	6592 lbs	6952 lbs	9208 lbs	8092 lbs	7741 lbs	9208 lbs	8092 lbs	7741 lbs		
Operating Weight	5202 lbs	6660 lbs	7625 lbs	7775 lbs	9347 lbs	9870 lbs	9975 lbs	9702 lbs	10308 lbs	10320 lbs	9702 lbs	10308 lbs	10320 lbs		
Travel Speed - High	N/A	N/A	N/A	N/A	N/A	N/A	N/A	6.6 mph	6.6 mph	6.1 mph	6.6 mph	6.6 mph	6.1 mph		
Travel Speed - Low	5.2 mph	7.3 mph	7.1 mph	7.1 mph	6.6 mph	6.6 mph	6.2 mph	6.6 mph	6.6 mph	6.1 mph	6.6 mph	6.6 mph	6.1 mph		
Ground Presssure (Rubber)	4.56 psi	5.2 psi	N/A	N/A	4 psi	4 psi	N/A	4.2 psi	4.2 psi	N/A	4.2 psi	4.2 psi	N/A		
Ground Pressure (Steel)	N/A	N/A	N/A	N/A	N/A	N/A	5.6 psi	N/A	N/A	5.8 psi	N/A	N/A	5.8 psi		
Fuel Tank	11.9 gal	15.4 gal	28 gal	28 gal	30 gal	30 gal	30 gal	30 gal	30 gal	30 gal	26 gal	26 gal	26 gal		
Cooling System	11.6 qt	12 qt	12 qt	11 qt	4.3 gal	4.3 gal	4.3 gal	4.3 gal	4.3 gal	4.3 gal	3.6 gal	3.6 gal	3.6 gal		
Pump Capacity	12.5 GPM	16.9 GPM	16.9 GPM	16.9 GPM	21.2 GPM	21.2 GPM	21.2 GPM	20.7 GPM	20.7 GPM	20.7 GPM	21.2 GPM	21.2 GPM	21.2 GPM		
Auxiliary High Flow	N/A	N/A	26.4 GPM	26.4 GPM	37 GPM	37 GPM	37 GPM	37 GPM	37 GPM	37 GPM	37 GPM	37 GPM	37 GPM		
Length	89.7 in	95.8 in	101.8 in	101.8 in	114.9 in	114.9 in	114.9 in	114.5 in	114.5 in	114.5 in	114.5 in	114.5 in	114.5 in		
Length with Standard Bucket	117 in	124.1 in	130.3 in	130.3 in	142.9 in	142.9 in	142.9 in	142.9 in	142.9 in	142.9 in	142.9 in	142.9 in	142.9 in		
Width	47.2 in	55 in	66 in	66 in	78 in	78 in	73.8 in	78 in	78 in	73.8 in	78 in	78 in	73.8 in		
Width (with bucket)	50 in	56 in	68 in	68 in	80 in	80 in	80 in	80 in	80 in	80 in	80 in	80 in	80 in		
Height	74.1 in	77.4 in	76.3 in	76.3 in	80.9 in	80.9 in	81.3 in	80.9 in	80.9 in	81.3 in	80.9 in	80.9 in	81.3 in		
Height with Operator Cab	74.1 in	77.4 in	76.3 in	76.3 in	80.9 in	80.9 in	81.3 in	80.9 in	80.9 in	81.3 in	80.9 in	80.9 in	81.3 in		
Height to Bucket Hinge Pin	103.7 in	109.6 in	114.5 in	118.2 in	122.4 in	122.4 in	122.8 in	128.8 in	128.8 in	128.8 in	128.8 in	128.8 in	128.8 in		
Reach @ Maximum Height	22.8 in	25.6 in	19.1 in	30.9 in	23.8 in	23.8 in	23.8 in	36.5 in	36.5 in	36.5 in	36.5 in	36.5 in	36.5 in		
Length of track on ground	51.1 in	48.4 in	55.2 in	55.2 in	63.7 in	63.7 in	58.9 in	63.7 in	63.7 in	58.9 in	63.7 in	63.7 in	58.9 in		
Track Width	9.8 in	11.8 in	12.6 in	12.6 in	18 in	18 in	13.4 in	18 in	18 in	13.4 in	18 in	18 in	13.4 in		
Track Width - Optional	N/A	N/A	16 in	16 in	12.6 in	12.6 in	N/A	N/A	N/A	N/A	12.6 in	12.6 in	N/A		
Attachment Hookup	2 Lever	N/A	Bob-Tach	Bob-Tach	Bob-Tach	Bob-Tach	Bob-Tach	Bob-Tach	Bob-Tach	Bob-Tach	Bob-Tach	Bob-Tach	Bob-Tach		
Joystick Control	n/a	n/a	opt	opt	opt	opt	opt	opt	opt	opt	opt	opt	opt		
Air Conditioning	n/a	n/a	opt	opt	opt	opt	opt	opt	opt	opt	opt	opt	opt		
Backup Alarm	std	std	std	std	std	std	std	std	std	std	std	std	std		
BICS System (Interlock)	std	std	std	std	std	std	std	std	std	std	std	std	std		
Cab Enclosure	opt	opt	opt	opt	opt	opt	opt	opt	opt	opt	opt	opt	opt		
Enclosed Operator Cab (ROPS/FOPS)	opt	opt	N/A	N/A	opt	opt	opt	N/A	N/A	N/A	N/A	N/A	N/A		
ROPS/FOPS Approved	yes	yes	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
Cab Heater	opt	opt	opt	opt	opt	opt	opt	opt	opt	opt	opt	opt	opt		
Heater Air Conditioning	N/A	n/a	N/A	N/A	opt	opt	opt	N/A	N/A	N/A	N/A	N/A	N/A		
Operating Lights	std	std	std	std	std	std	std	std	std	std	std	std	std		
Suspension Seat	std	std	std	std	std	std	std	opt	opt	opt	opt	opt	opt		
Two Speed Travel	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a		
Deluxe Instrumentation	n/a	opt	opt	opt	opt	opt	opt	opt	opt	opt	opt	opt	opt		
Engine Shutdown	std	std	std	std	std	std	std	std	std	std	std	std	std		
Hydraulic Bucket Positioning	opt	opt	opt	opt	opt	opt	opt	opt	opt	opt	opt	opt	opt		
High Flow Option	n/a	n/a	opt	opt	opt	opt	opt	opt	opt	opt	opt	opt	opt		
Bob-Tach Attachment System	std	std	std	std	std	std	std	std	std	std	std	std	std		
Power Bob-Tach	n/a	opt	opt	opt	opt	opt	opt	opt	opt	opt	opt	opt	opt		
ACS (Switchable Controls)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
ROPS Approval	N/A	std	N/A	N/A	std	std	std	N/A	N/A	N/A	N/A	N/A	N/A		
Horn	std	std	std	std	std	std	std	std	std	std	std	std	std		